

# Advanced System Display and Controller MATE3



## Description

- Program, Manage and Monitor Entire System
- User Friendly Interface
- Intuitive Menu Structure
- Easy-To-Read Graphical Display
- System Configuration Wizard
- Internet Enabled
- Field Upgradable
- Up to 1-Year of Data Logging
- SD Memory Card Slot

The new MATE3 System Display and Controller makes it easier than ever to program and monitor your complete OB Power system. An intuitive user interface and integrated system configuration wizard make system setup and programming quick and seamless. The ability to set unique multi-level user passwords allows you to secure critical system settings from unintended changes while still allowing open access to necessary functions. Through the use of a single MATE3 you can remotely manage and monitor multiple inverter/chargers, charge controllers and DC monitoring devices.

The MATE3 is packed full of features to make system management simple. The easy-to-read graphical LCD display is backlit for dark operating conditions. Improved tactile buttons and a user programmable "favorite" key give you immediate access to the features you want, while an intuitive scroll wheel interface allows for easy adjustment of system setpoints. Expandable SD card memory allows you to increase data logging capacity as well as upgrade units in the field.


A built-in clock and calendar function enables timer-based programming of inverter and charger operation. This permits you to set the system to work with time-of-day power rates or to limit a generator's run time to a specific time period of the day or week. All of your settings are stored in permanent memory to eliminate the need to reprogram in the event of a system shutdown or battery replacement. The MATE3 is an Internet enabled device connecting to the Internet will allow full remote system monitoring via an easy-to-use web interface.

The MATE3 system display and controller is the next generation of communication interface, offering powerful insight into every aspect of your OB Power system.

## Specifications ( Specifications Subject to Change Without Notice )

Display	10 x 3cm full graphical display
Quick System Access	5 system operation hot keys, 1 user programmable hot key
Status Indicators	Nine LED Status Indicators
Navigational Controls	5 navigational keys
Setpoint Adjustment	Touch sensitive scroll wheel
Communication Protocol	Proprietary OB Communications Protocol
Interconnection Cabling	Standard CAT 5 network cable with RJ45 modular jack 2 m included
PC Computer Interface	Ethernet
Microprocessor	80 MHz 32 bit processor
Setpoint and Data Memory	8Mb RAM/ 64Mb of flash RAM
Clock / Calendar	On-board real time clock with battery backup
Environmental Rating	Indoor Type 1 (IP 30)
Storage- Operating Temperature	0 to +50°C
Maximum Cable Length	100 m

### Available from:



## RIPEnergy®

The power conversion company



RIPEnergy AG  
Wägitalstrasse 24  
CH-8854 Siebnen  
Switzerland

Ph +41-(0)43-818 53 85  
Fax +41-(0)43-818 53 87  
www.ripenergy.ch