



IVSrail1000P RAILWAY SINE WAVE INVERTER

SERIES IVSrail1000P

This rugged, railway quality DC/AC inverter uses field proven, microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage.

The unit meets the requirements of EN50155 for electronic equipment used on railway rolling stock. It is a mature design with a track record in numerous applications.

The DC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output.

The use of high frequency conversion enables a compact construction, low weight and high efficiency.

The input and output are filtered for low noise.

The unit has full electronic protection.

It is built with internal power modules that are entirely potted with a thermally conductive MIL-grade silicon rubber compound to ensure immunity to high levels of shock, vibration and humidity.

Cooling is via baseplate to a cold plate surface and by additional natural convection.

The use of components with established reliability results in high MTBF.

All of our products are manufactured at our plant under strict quality control.

Customized versions are available

APPLICATIONS

- Railway Applications
- Industrial Controls
- Telecom Power Plants
- Marine & other rugged environments
- Electric Utilities and Substations
- Base Station Power

FEATURES

- Sine wave output voltage
- Fully encapsulated internal modules
- Field-proven rugged design
- Conduction / convection cooled, no fan
- Low profile
- Compact size
- Designed for rolling applications according to EN50155
- Full electronic protection



Pure Sinewave



High frequency technology



Light weight, compact size



Full electronic protection



Extended temperature range



Conduction convection cooled



Optional Output fail alarm (Form C)

SPECIFICATIONS

Input Voltage	24Vdc (17-34V) 36Vdc (25-51V) 48Vdc (33-67V) 72Vdc (50-101V) 96Vdc (67-135V) 110Vdc (77-154V) Consult factory for other inputs
Input Protection	Inrush current limiting Varistor Reverse polarity protection Internal safety fuse Lower voltage than the specified minimum input will not damage the unit
Isolation	1500VDC Input to chassis 3000VDC Input to output
Output Voltage	230Vac @ 50Hz/4.3A rms continuous or 115Vac @ 60Hz or 400Hz/8.7A rms continuous Output neutral is connected to the chassis internally Isolated floating output optional Consult factory for other output requirements
Output Wave Form	Sinusoidal
Total Harmonic Distortion	Less than 5% at full load
Line / Load Regulation	± 6% from 5% to full load
Load Crest Factor	2.0 at 90% load
Output Ripple Noise	High frequency ripple is less than 500mVrms (20MHz BW)
Efficiency	Typically 80% at full load Dependent on input/output combination
Output Overload Protection	Current limiting with short circuit protection Thermal shutdown with automatic recovery in case of insufficient cooling
Output Overvoltage Protection	270Vac (for 230Vac output) or 140Vac (for 115Vac output) by internal supply voltage limiting

Standards	Designed to meet C22.2 No. 107.1 - 01, UL 458, EN62368-1 and EN50155
EMI	EN50121-3-2
Immunity	Meets criteria of EN50155 and EN50121-3-2 including EN 61000-4-2 (ESD) EN61000-4-3 (RF Immunity) EN61000-4-4 (Fast transients) EN50155 (Surge) EN61000-4-6 (Conducted Imm.) EN50155 (Voltage Variations)
Operating Temperature	-25 to +55°C cold-plate temperature for full specification Extended temperature range available on request
Humidity	5 - 95% non-condensing
Temperature Drift	0.05% per °C over operating temperature range
Cooling	Conduction to customer heat sink or chassis
Environmental Protection	Tray potted internal modules
Shock/Vibration	IEC 61373 Cat 1 A&B
Dimensions	F31: 483 x 68 x 356 mm (W x H x L) including terminal block and flanges Mounting holes are clear
Weight	approx. 9 Kg
Connections	Input: Terminal block Output: Terminal block
MTBF	150,000 hours at 45°C Demonstrated MTBF is significantly higher
Indicators	None
Control Input	None Optional remote shut down
Alarm output	None Optional output Fail Alarm (Form C)
RoHS Compliance	Fully compliant
Warranty	2 years

Terminal Block Pin-out

